

Product group: 195 Product number: 655266

Welding cable 95 mm², sold per meter basis



Product information

This product supersedes product no: L15268

Welding cables used on board, on deck or in an engine room, are exposed to rough weather, oil and mechanical wear. The welding cable supplied by Unitor has wear, flame and oil-resistant insulation on a polychloroprene rubber basis. It is recognized by its marking at regular intervals with the text "Unitor oil resistant welding cable", size of cable, and the standard for welding cable H01N2-D. H01N2-D means that the cable is produced to an international harmonized standard. The conductor is built up from 0.2mm diameter tinned copper strands to ensure flexibility. The cable is available in cross section areas 35mm², 50mm² 70mm², and 95mm².

Features

- Unitor welding cable is oil resistant, flame resistant and wear resistant. The conductor is built up from 0.2mm diameter copper wires to ensure high flexibility
 -
- The Unitor welding cable complies with the harmonised standard HO1N2D for flexible welding cable

Specification

General		Dimensions/Weight	
Invent Hazard Material (IMO/EU) classification	NA	Weight [kg]	1.06
Performance data			
Amperage [A]			

Documents

[SDoC and MD for IHM](#)

Related products

Is frequently bought together with

- 699405**
18/8-321N 2.5X300MM89 PCS 1.7 KG
- 699462**
DUPLEX-325N 3.2X350MM55 PCS 2.0 KG
- 699454**
DUPLEX-325N 2.5X300MM91 PCS 1.7 KG
- 619098**
FACE SHIELD W/HANDLE