

Product group: **196**    Product number: **633289**

Filter glasses for arc welding

## Product information

This product supersedes product no: **175703**

For use from 300-500 amp, the glasses have dimension 60 x 110 mm and are manufactured in accordance with DIN standard and are CE approved. When ordering face shields, filter shade glass of correct shade should be ordered in addition to the filter shade 11 glasses which are included. The filter glasses are supplied in sets consisting of 5 safety glasses, 5 protection glasses and 5 filter shade glasses.



## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
--	----

## Approvals

CE

## Documents

[SDoC and MD for IHM](#)

## Directions for use

<b>A. Safety glass (polycarbonate)</b>
The glass is used in shields with a flip-up front frame and should be placed nearest to the eyes to protect against slag or other articles while chipping/ grinding when the flip up front is open.
<b>B. Filter shade glass</b>
Filters out harmful infra-red and ultra-violet rays from the welding arc, and reduces visible light to a level which is sufficient to see the welding process without straining the welder's eyes. Filter Shade Glass should be selected based on welding process and amperage. The glasses are marked Protane Shade SO 1 DIN 0196 CE
<b>C. Protection glass</b>
The glass is placed in front of the filter shade glass to protect against spatter. The protection glass should be replaced at regular intervals.

## Related products

### Is accessory to

**709485**  
FLIPVISION WELDING FACE SHIELD

**619098**  
FACE SHIELD W/HANDLE

**619114**  
SAFETY HELM W/FACE SH.

### Is frequently bought together with

**510000**  
REGULATOR 510 OX PRESSURE 0-10 BAR

**633263**  
SHADE 11 GLASS. 5SET

**175273**  
WELD.GOGGLES W/LIFT-FRONT

**632786**  
WELDERS GLOVES. 6 PAIRS

**633271**  
SHADE 12 GLASS. 5 SET

**This page is printed from:**

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-equipment/welders-protection/shade-13-glass.-5-set>