

Product group: **096** Product number: **653535**

Magnaflux crack detection kit comes in a convenient shoulder carrying bag.

Product information

This product supersedes product no: L52568

Magnaflux Crack Detection Kit is an easy to use, cost effective and non-destructive inspection method to detect cracks and porosities especially for welding.

The kit contains: 3 pcs cleaner spray cans 2 pcs penetrant spray cans 3 pcs developer spray cans 1 pc cloth

Specification

General



Documents

SDoC and MD for IHM

Directions for use

Step 1) Remove surface rust, scale, paint by mechanical means, spray cleaner to degrease the inspection area. Leave to dry.

Step 2) Spray penetrant over the area and allow to soak for about ten minutes.

Step 3) Remove all excess penetrant using a dry cloth and wipe dry.

Step 4) Spray developer evenly over the inspection area and wait a few minutes until the area dries white. Any surface defects will appear in red contrast.

Related products

Is frequently bought together with

632984

WIRE BRUSH STAINL. 6PCS

699264

LH-314N 2.5X350MM 161 PCS 4.0 KG

661778

PICKLING GEL 2L F/STAINLESS STEEL

526015

SAFE GRINDER 42V FOR WELDING MACHINES

This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-equipment/welders-tools/magnaflux-crack-detection-kit-323/2009.

