

Product group: 103 Product number: 659292

Two components (liquid based), solvent free, cold curing vulcanising fluid for repair of rubber items or on metal surfaces.



Product information

This product supersedes product no: 606013

Application include used on hoses, gaskets, rubber rollers, ducting, impellers, valves etc.

Safety Notice: This product contain di-isocyanates.

The European Commission has amended AnnexXVI to the REACH Regulation (new entry 74) with Regulation (EU) 2020/1149. Accordingly, starting August 2023, adequate mandatory health & safety training is required before industrial or professional use of product with di-isocyanates.

Training website suggestion: <https://www.safeusediisocyanates.eu/>

Features

- Can be used for most types of rubber and metals
- Synthetic rubber compound
- Product in fluid state
- Does not produce any heat during curing
- Comes with SDS, tech sheet, gloves and application tools

Benefits

- No need to consider base material
- Multit-purpose
- Can be applied using a brush
- No sparks and spatter that can create a fire or explosion
- No distortion of the base material
- Accessories included

Specification

General		Dimensions/Weight	
Invent Hazard Material (IMO/EU) classification	NA	Weight [kg]	0.59

Technical data

A two component cold-curing vulcanising repair fluid that can be moulded or painted on to rubber or metallic surfaces. Set of 3 x 0,143 l Engineering Repair Fluid.

Documents

[SDoC and MD for IHM](#)

Related products

Is consumable by
COLD REPAIR POLYMER COMPOUNDS

Is frequently bought together with
659276
CERAMIGRADE LINER