

Product group: 176 Product number: 576157

1/4" (6.3mm) black hose for shielding gas use i.e., with Argon or Argon/CO2.



Product information

Unitor's hoses for welding gases are made according to ISO 3821 / European Norm EN 559.

Normal working pressure up to 20 bar.
Test pressure 40 bar
Minimum bursting pressure 60 bar

The hoses are colour-coded red for acetylene, blue for oxygen and black for shielding gases.

UNITOR's hoses for acetylene and oxygen are specially made for use with welding and cutting equipment.

Features

- Order are by per meter. Favourite length per order i.e., 10m or 50m coil
- Single hose for shielding gas supply made according to ISO 3821 / European Norm EN 559

Benefits

Made with the highest safety in mind i.e.:

- High ignition temperature synthetic rubber
- High tensile synthetic textile filament yarn
- Excellent ozone and weather resistant synthetic rubber

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[DoC - 576158 Gas Hose Black](#)

[SDoC and MD for IHM](#)

Related products

Is accessory to

- 320320
UWI-320TP WELDING INVERTER
- 500102
UWF-102 WIRE FEEDER FOR UWI-500TP
- 320201
QUICK COUPLING AR HOSE TO HOSE 6MM
- 203203
UWI-203 TP WELDING INVERTER
- 301301
UWW-301 TP WIRE WELDER
- 320202
QUICK COUPLING AR REG. TO HOSE 6MM

Is frequently bought together with

- 510010
REGULATOR 510 AR/CO2 FLOW 0-35L/MIN
- 510420
LEATHER APRON F/WELDING
- 674710
TUNGSTEN EL. 1.6MM 10PCS
- 175596
HOSE JOINT F/6MM(1/4 INCH) OX HOSE
- 607810
TIG TORCH ACCESSORIES KIT

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/gas-hoses-and-couplings/gas-hose-14-6.3mm-black>