

Product group: 093 Product number: 519744

Bare silver brazing rod for most metals and able to use on larger joint gap up to 1.0mm.

Product information

Silver solder (44% silver) for capillary brazing of all types of steel, copper alloys, nickel alloys, cast steel etc. Does not contain cadmium. Should not be used on seawater piping like cunifer or yorcalbro, where a silver content of minimum 50% is needed. Use with AG-45/60 Brazing FluxBAF.

Features

- Unique chemistry give high strength
- Cadmium and Phosphorus free, suitable for marine use
- Low melting point

Benefits

- Less possibility for joint to fail during operation
- Safe to use
- Job is done faster

Specification

General

Invent Hazard Material (IMO/IU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

Directions for use

The label on each container fully identifies the contents, and also gives basic information on application areas. Complete information on each rod, and instructions for use are given in the handbook for Maritime Welders.

Flame setting: Use neutral flame

Related products

Is part of bundle

589861
GASWELDING CABINET COMPLETE

Is frequently bought together with

699264
LH-314N 2.5X350MM 161 PCS 4.0 KG
699165
GPO-302N 2.5X350MM 295 PCS 5,2KG
233601
AG 60 252 2.0 X 500MM 0,5KG
233604
AG 45/60 BRAZING FLUX BAF.250G

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/gas-welding-and-brazing-consumables/ag-45-253-2.0-x-500mm-04kg/>

