

Product group: 092 Product number: 603043

Flux for use together with Alumag 235 when doing Gas and TIG Welding.

Product information

White flux in powder form inside container.

Aluminum welding flux is designed to remove the aluminum oxide film and exclude oxygen from the vicinity of the puddle.



Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

Directions for use

The label on the container fully identifies the contents, and also gives basic information on application areas. Complete information on each flux label, and instructions for use are given in the handbook for Maritime Welders.

Apply with brush. on rod and joint edges. The flux is corrosive. Remove with brush and hot water after brazing.

Related products

Is part of bundle

589861
GASWELDING CABINET COMPLETE

Is frequently bought together with

- 514265
ALUMAG 235 3.0MM GAS TIG WELD 0.5KG
- 174706
CUTTING NOZZLE 10- 25MM
- 174698
CUTTING NOZZLE 3- 10MM
- 699264
LH-314N 2.5X350MM 161 PCS 4.0 KG
- 233601
AG 60 252 2.0 X 500MM 0,5KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/gas-welding-and-brazing-consumables/aluflux-234-f.-250-g>