

CAST IRON FLUX 236 F. 250 G

Product group: **092** Product number: **764487**

Flux can be use on Cast Iron 237 rod for brazing of Cast Iron and also TIG welding of Ialbro-237MF rod.



Product information

Flux in powder form inside container. Apply by sticking the cast iron rod that has been heated at the end into the powder. The flux will stick to the hot rod in sufficient quantity for successful welding. The flux is corrosive. Remove with brush and hot water after brazing.

Features

- Sealed flux containers
- Long shelf life
- In powder form

Benefits

- Prevent contamination and upkeep high quality
- Protect investment
- Ready for use.

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Directions for use

The label on the container fully identifies the contents, and also gives basic information on application areas. Complete information on each flux label, and instructions for use are given in the handbook for Maritime Welders.

Related products

Is part of bundle

589861 GASWELDING CABINET COMPLETE

Is frequently bought together with

233601	AG 60 252 2.0 X 500MM 0,5KG	602979	18/8MO-221 2.0 X 500 MM 0,5KG
335547	ICUNI-30 239 2.5 X 500 MM 2,0KG		
604850	IMS-210 2.0 X 500 MM 1,5KG		
305532	ICROMO-216 2.5 X 500 MM 1,0KG		

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/gas-welding-and-brazing-consumables/cast-iron-flux-236-f.-250-g/>