

Last updated: 23/04/2024 01:00:49

CAST IRON FLUX 236 F. 250 G

Product group: **092** Product number: **764487**

Flux can be use on Cast Iron 237 rod for brazing of Cast Iron and also TIG welding of Ialbro-237MF rod.



Product information

Flux in powder form inside container.

Features

- Sealed flux containers
- Long shelf life
- In powder form

Benefits

- Prevent contamination and upkeep high quality
- Protect investment
- Ready for use.

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

Directions for use

The label on the container fully identifies the contents, and also gives basic information on application areas. Complete information on each flux label, and instructions for use are given in the handbook for Maritime Welders.

Apply by sticking the cast iron rod that has been heated at the end into the powder. The flux will stick to the hot rod in sufficient quantity for successful welding. The flux is corrosive. Remove with brush and hot water after brazing.

Related products

Is part of bundle

589861
GASWELDING CABINET COMPLETE

Is frequently bought together with

233601
AG 60 252 2.0 X 500MM0,5KG

305532
ICROMO-216 2.5 X 500 MM1,0KG

604850
IMS-210 2.0 X 500 MM1,5KG

602979
18/8MO-221 2.0 X 500 MM0,5KG

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/gas-welding-and-brazing-consumables/cast-iron-flux-236-f.-250-g>