

Product group: 093      Product number: 233569

Flux coated brazing rod for copper, copper alloys and steel.

Product information

Flux-coated bronze rod with low bonding temperature and high tensile strength for joining and overlaying copper, brass, bronze, cast iron and steels. Galvanized steel may be braze- welded with FC-bronze without damaging the galvanizing. When additional flux is needed Unitor Bronzeflux - 261 PF should be used.

Features

- High tensile strength
- Low melting point
- Good melting flow

Benefits

- Job is done faster and very user friendly
- Galvanized pipes can be brazed without destroying galvanizing

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

Directions for use

The label on each container fully identifies the contents, and also gives basic information on application areas. Complete information on each rod, and instructions for use are given in the handbook for Maritime Welders.

Flame setting: Use neutral or slight oxygen surplus

Related products

Is part of bundle

589861  
GASWELDING CABINET COMPLETE

Is frequently bought together with

699264  
LH-314N 2.5X350MM 161 PCS 4.0 KG

699165  
GPO-302N 2.5X350MM 295 PCS 5,2KG

233551  
FC-BRONZE 261 2.0 X500MM 1,0KG

233601  
AG 60 252 2.0 X 500MM 0,5KG

603076  
BRONZE-FLUX 261 PF. 250G

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/gas-welding-and-brazing-consumables/fc-bronze-261-3.0-x-500mm-10kg/>

