

Product group: 092 Product number: 539569

Gas welding rod for steel.

Product information

Gas welding rod for unalloyed steels and low alloyed structural steel with a carbon content of less than 0.2%. Tensile strength 390-440 N/mm2.

Gas welding may be used for up to 6 mm thickness. For larger dimensions electric arc welding is recommended.

Features

- Copper coated
- Low silicon content
- Can be used for thin as well as heavier sheets

Benefits

- Prevent rusting during storing
- Fluid molten pool makes welding easy
- Large working range
- No flux required

Specification

General		Technical data	
Invent	Hazard Material (IMO/IU) classification	NA	
		AWS	A5.2: R60

Documents

[SDoC and MD for IHM](#)

Directions for use

Flame setting: Use neutral flame

Related products

Is part of bundle

589861
GASWELDING CABINET COMPLETE

Is frequently bought together with

510001
REGULATOR 510 AC PRESSURE 0-1.5 BAR

699173
GPO-302N 3.2X350MM 190 PCS 5.4 KG

539551
MS-200 2.0 X500M3,5KG

603076
BRONZE-FLUX261 PF. 250G

233601
AG 60 252 2.0 X500MM0,5KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/gas-welding-and-brazing-consumables/ms-200-3.0-x-500mm-35kg/>

