

Last updated: 19/06/2023 10:33:12

# MS-200 3.0 X 500MM 3,5KG

Product group: **092** Product number: **539569**

Gas welding rod for steel.



## Product information

Gas welding rod for unalloyed steels and low alloyed structural steel with a carbon content of less than 0.2%. Tensile strength 390-440 N/mm<sup>2</sup>.

Gas welding may be used for up to 6 mm thickness. For larger dimensions electric arc welding is recommended.

### Features

- Copper coated
- Low silicon content
- Can be used for thin as well as heavier sheets

### Benefits

- Prevent rusting during storing
- Fluid molten pool makes welding easy
- Large working range
- No flux required

## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
--	----

### Technical data

AWS	A5.2: R60
-----	-----------

## Documents

[SDoC and MD for IHM](#)

## Directions for use

Flame setting: Use neutral flame

## Related products

Is part of bundle

**589861**  
GASWELDING CABINET COMPLETE

Is frequently bought together with

**510001**  
REGULATOR 510 AC PRESSURE 0-1.5 BAR

**699173**  
GPO-302N 3.2X350MM 190 PCS 5.4 KG

**539551**  
MS-200 2.0 X 500M 3,5KG

**603076**  
BRONZE-FLUX261 PF. 250G

**233601**  
AG 60 252 2.0 X 500MM 0,5KG

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing-cutting/gas-welding-and-brazing-consumables/ms-200-3.0-x-500mm-35kg>