

Last updated: 19/06/2023 10:33:16

# TIN 241 AG 1.5 MM 0.5 KG SOLDER

Product group: **093** Product number: **777973**

Flux cored lead free silver alloyed soft solder wire on spool.

## Product information

This product supersedes product no: **305342**

Soft solder on spool. The lead free tin incorporates five ducts filled with high quality flux. This tin is silver alloyed for high quality result.

For tinning and joining of electric conductors, electrical connections, electrical instruments, radios, batteries, refrigeration plants, etc.

### Features

- Lead free
- Flux cored wire
- Low melting point

### Benefits

- Non poisonous
- No need for additional flux
- Less heat needs to be applied, thereby avoiding overheating surrounding components

## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
------------------------------------------------	----



## Documents

[SDoC and MD for IHM](#)

## Directions for use

Additional flux not needed. Use soldering iron or soft flame with acetylene surplus.

## Related products

Is part of bundle

**589861**  
GASWELDING CABINET COMPLETE

Is frequently bought together with

**233601**  
AG 60 252 2.0 X 500MM 0,5KG

**699165**  
GPO-302N 2.5X350MM 295 PCS 5,2KG

**699264**  
LH-314N 2.5X350MM 161 PCS 4.0 KG

**233551**  
FC-BRONZE 261 2.0 X 500MM 1,0KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/gas-welding-and-brazing-consumables/tin-241-ag-1.5-mm-0.5-kg-solder>