Last updated: 30/04/2025 05:20:59



CUTTING ATTACHMENT 75 DGR

Product group: 170 Product number: 174664

Cutting attachment 75 degrees for connecting to shank when doing oxy/acetylene cutting operations.

Product information

Accessories for UCT-500 cutting torch.

Features

- Adjustable towards shank
- Slim and simple design
- Equipment conform to EN/ISO 5172

Benefits

- · Able to reach difficult locations
- · Less strain on operator
- · Provides safety and long lasting quality

Specification

General

Invent Hazard Material (IMO/EU) classification

NΑ

Documents

SDoC and MD for IHM

Related products

Accessories

174730

GOUGING NOZZLE

174722

CUTTING NOZZLE 50-100MM

174698

CUTTING NOZZLE 3- 10MM

183855

CUTTING NOZZLE 140MM LENGTH 40-75MM

174706

CUTTING NOZZLE 10-25MM

174714

CUTTING NOZZLE 25-50MM

174672

ROLLER GUIDE STANDARD

174680

CIRCULAR MOTION BAR

CUTTING NOZZLE 153MM LENGTH 25-40MM

Is frequently bought together with

905026

ACETYLENE A-40 FILLING

905034

OXYGEN O-40 FILLING

174656

SHANK W/NON-RETURN VALVES

510000

REGULATOR 510 OX PRESSURE 0-10 BAR

REGULATOR 510 AC PRESSURE 0-1.5 BAR



This page is printed from

https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/cutting-attachment-75-dgr/