

Product group: **170** Product number: **174664**

Cutting attachment 75 degrees for connecting to shank when doing oxy/acetylene cutting operations.

Product information

Accessories for UCT-500 cutting torch.

Features

- Adjustable towards shank
- Slim and simple design
- Equipment conform to EN/ISO 5172

Benefits

- Able to reach difficult locations
- Less strain on operator
- Provides safety and long lasting quality

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

Related products

Accessories

- 174730**
GOUGING NOZZLE
- 174722**
CUTTING NOZZLE 50-100MM
- 174698**
CUTTING NOZZLE 3- 10MM
- 183855**
CUTTING NOZZLE 140MMLLENGTH 40-75MM
- 174706**
CUTTING NOZZLE 10- 25MM
- 174714**
CUTTING NOZZLE 25- 50MM
- 174672**
ROLLER GUIDE STANDARD
- 174680**
CIRCULAR MOTION BAR
- 183863**
CUTTING NOZZLE 153MMLLENGTH 25-40MM

Is frequently bought together with

- 905026**
ACETYLENE A-40 FILLING
- 905034**
OXYGEN O-40 FILLING
- 174656**
SHANK W/NON-RETURN VALVES
- 510000**
REGULATOR 510 OX PRESSURE 0-10 BAR
- 510001**
REGULATOR 510 AC PRESSURE 0-1.5 BAR

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/cutting-attachment-75-dgr/>