

Product group: 170 Product number: 174664

Cutting attachment 75 degrees for connecting to shank when doing oxy/acetylene cutting operations.

NA

## **Product information**

Accessories for UCT-500 cutting torch.

#### Features

- Adjustable towards shank
- Slim and simple designEquipment conform to EN/ISO 5172
- Benefits
- . . .
- Able to reach difficult locationsLess strain on operator
- Provides safety and long lasting quality

## **Specification**

### General

Invent Hazard Material (IMO/EU) classification

## **Documents**

SDoC and MD for IHM

## **Related products**

# Accessories

174730 GOUGING NOZZLE 174722 CUTTING NOZZLE 50-100MM 174698 CUTTING NOZZLE 3-10MM 183855 CUTTING NOZZLE 140MM LENGTH 40-75MM 174706 CUTTING NOZZLE 10-25MM 174714 CUTTING NOZZLE 25-50MM 174672 ROLLER GUIDE STANDARD 174680 CIRCULAR MOTION BAR 183863 CUTTING NOZZLE 153MM LENGTH 25-40MM

# Is frequently bought together with

905026 ACETYLENE A40 FILLING 905034 OXYGEN O-40 FILLING 174656 SHANK W/NON-RETURN VALVES 510000 REGULATOR 510 OX PRESSURE 0-10 BAR 510001 REGULATOR 510 AC PRESSURE 0-1.5 BAR

#### This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/cutting-attachment-75-dgr/

