

Product group: 170 Product number: 183855

The cutting nozzles are specially made for use with UCT-500 gas cutting equipment and with oxy/acetylene gases.



Product information

Nozzles should be selected based on cutting thickness. The basic information is marked directly on the nozzle i.e.:

Nozzle length 140mm Material thickness 40-75 mm Gas consumption OX: 5230nl/h AC: 570nl/h

Features

- Designed for use with oxy/acetylene
- Made from high quality copper alloys
- Machined to precision for correct seating angle to prevent any gas leakages and uniform gas holes

Benefits

- Made with the highest safety in mind for equal pressure torch
- Good cutting performance
- Durable

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

234807
CUTTING ATTACHMENT 90 DGR
174664
CUTTING ATTACHMENT 75 DGR

Is frequently bought together with

174706
CUTTING NOZZLE 10- 25MM

174730
GOUGING NOZZLE

174698
CUTTING NOZZLE 3- 10MM

174326
BRONZE-264 3.0 X500MM 1,7KG

905034
OXYGEN O-40 FILLING

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/cutting-nozzle-140mm-length-40-75mm/>