

Last updated: 30/04/2025 05:20:10



# CUTTING NOZZLE 153MM LENGTH 25-40MM

# Product group: **170** Product number: **183863**

The cutting nozzles are specially made for use with UCT-500 gas cutting equipment and with oxy/acetylene gases.

# **Product information**

Nozzles should be selected based on cutting thickness. The basic information is marked directly on the nozzle i.e.:

Nozzle length 153mm Material thickness 25-40 mm Gas consumption OX: 3800nl/h AC: 490nl/h

#### Features

- Designed for use with oxy/acetylene
- Made from high quality copper alloys
- Machined to precision for correct seating angle to prevent any gas leakages and uniform gas holes

### Benefits

- Made with the highest safety in mind for equal pressure torch
- Good cutting performance
- Durable

# Specification

#### General

Invent Hazard Material (IMO/EU) classification

NA

# **Documents**

SDoC and MD for IHM

## **Related products**

Is accessory to 174664 CUTTING ATTACHMENT 75 DGR 234807 CUTTING ATTACHMENT 90 DGR

This page is printed from

https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/cutting-nozzle-153nm-length-25-40nm/welding-brazing--cutting-brazing--cutting-brazing--cutting-torch/cutting-nozzle-153nm-length-25-40nm/welding-brazing--cutting--brazing--cutting--brazing--cutting--brazing--cutting--brazing--cutting--cutting--cutting--cutting--cutting--cutting--cutting--cutting--cutting--

