

Product group: **170** Product number: **174714**

The cutting nozzles are specially made for use with UCT-500 gas cutting equipment and with oxy/acetylene gases.

Product information

Nozzles should be selected based on cutting thickness. The basic information is marked directly on the nozzle i.e.:

Nozzle no 4

Material thickness: 25-50 mm Gas consumption OX: 5650nl/h AC: 690nl/h

Features

- Designed for use with oxy/acetylene
- Made from high quality copper alloys
- Machined to precision for correct seating angle to prevent any gas leakages and uniform gas holes

Benefits

- Made with the highest safety in mind for equal pressure torch
- Good cutting performance
- Durable

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

[cutting-nozzle](#)

Related products

Is accessory to

500000
UCT-500 COMBINATION TORCH MASTER
234807
CUTTING ATTACHMENT 90 DGR
174664
CUTTING ATTACHMENT 75 DGR
234815
CUTTING ATTACHMENT 0 DGR

Is part of bundle

589861
GASWELDING CABINET COMPLETE

Is frequently bought together with

510001
REGULATOR 510 AC PRESSURE 0-1.5 BAR
510000
REGULATOR 510 OX PRESSURE 0-10 BAR
699173
GPO-302N 3.2X350MM 190 PCS 5.4 KG
174706
CUTTING NOZZLE 10- 25MM
174698
CUTTING NOZZLE 3- 10MM

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/cutting-nozzle-25--50mm/>