

Product group: 170 Product number: 174722

The cutting nozzles are specially made for use with UCT-500 gas cutting equipment and with oxy/acetylene gases.



Product information

Nozzles should be selected based on cutting thickness. The basic information is marked directly on the nozzle i.e.:

Nozzle no 5 Material thickness 50-100 mm Gas consumption OX: 7800nl/h
AC: 810nl/h

Features

- Designed for use with oxy/acetylene
- Made from high quality copper alloys
- Machined to precision for correct seating angle to prevent any gas leakages and uniform gas holes

Benefits

- Made with the highest safety in mind for equal pressure torch
- Good cutting performance
- Durable

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[cutting-nozzle](#)

[SDoC and MD for IHM](#)

Related products

Is accessory to

- 500000
UCT-500 COMBINATION TORCH MASTER
- 234807
CUTTING ATTACHMENT 90 DGR
- 234815
CUTTING ATTACHMENT 0 DGR
- 174664
CUTTING ATTACHMENT 75 DGR

Is part of bundle

- 589861
GASWELDING CABINET COMPLETE

Is frequently bought together with

- 510001
REGULATOR 510 AC PRESSURE 0-1.5 BAR
- 510000
REGULATOR 510 OX PRESSURE 0-10 BAR
- 174706
CUTTING NOZZLE 10- 25MM
- 174698
CUTTING NOZZLE 3- 10MM
- 174714
CUTTING NOZZLE 25- 50MM

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/cutting-nozzle-50-100mm/>