



FLEX.WELD.ATTACHMENT 160L

Product group: **170** Product number: **183780**

Size* 160 Material thickness 1-2mm. This attachment can be bent to any desired shape.



Product information

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Technical data

Size indicates consumption of oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

Variants

Product name	Product number
<u>FLASHBACK ARRESTOR FR-20 FOR AC+OX</u>	619270
<u>FLEX.WELD.ATTACHMENT 160L</u>	183780
<u>HEATING ATTACHMENT 5000 L</u>	183756
<u>MULTIFLAME HEATING ATTACHMENT 5000L</u>	603399
<u>SHANK NONRETURN VALVE F/6MM AC HOSE</u>	597336
<u>SHANK NONRETURN VALVE F/6MM OX HOSE</u>	597344
<u>SHANK NONRETURN VALVE F/9MM AC HOSE</u>	651265
<u>SHANK NONRETURN VALVE F/9MM OX HOSE</u>	651257
<u>SHANK W/NON-RETURN VALVES</u>	174656
<u>WELDING ATTACHMENT 1000 L</u>	174615
<u>WELDING ATTACHMENT 1250 L</u>	174623
<u>WELDING ATTACHMENT 230 L</u>	174581
<u>WELDING ATTACHMENT 40 L</u>	174565
<u>WELDING ATTACHMENT 400 L</u>	174599
<u>WELDING ATTACHMENT 650 L</u>	174607
<u>WELDING ATTACHMENT 80L</u>	174573

Related products

Is frequently bought together with

174698	CUTTING NOZZLE 3- 10MM	174706	CUTTING NOZZLE 10- 25MM
500000	UCT-500 COMBINATION TORCH MASTER	233551	FC-BRONZE 261 2.0 X500MM 1,0KG
150000	TIG TORCH T-150 W.DIX 25 CONNECTOR		

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/flex.weld.attachment-160/>