

Product group: 170 Product number: 174730

The gouging nozzles are specially made for use with UCT-500 gas cutting equipment and with oxy/acetylene gases.



Product information

The basic gouging information is marked directly on the nozzle i.e.:

Furrow width 8-11 mm Furrow depth 6-11 mm Gas consumption OX:11500nl/h AC:1750nl/h

Features

- Designed for use with oxy/acetylene
- Made from high quality copper alloys
- Machined to precision for correct seating angle to prevent any gas leakages and uniform gas holes

Benefits

- Made with the highest safety in mind for equal pressure torch
- Good gouging performance
- Durable

Specification

General

Invent Hazard Material (IMO/IU) classification	NA
------------------------------------------------	----

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

- 234807
CUTTING ATTACHMENT 90 DGR
- 174664
CUTTING ATTACHMENT 75 DGR
- 234815
CUTTING ATTACHMENT 0 DGR

Is frequently bought together with

- 510000
REGULATOR 510 OX PRESSURE 0-10 BAR
- 174706
CUTTING NOZZLE 10- 25MM
- 174698
CUTTING NOZZLE 3- 10MM
- 632786
WELDERS GLOVES. 6 PAIRS
- 174714
CUTTING NOZZLE 25- 50MM

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/gouging-nozzle/>