

Last updated: 23/07/2025 01:00:49

# WELDING ATTACHMENT 1250 L

Product group: **170** Product number: **174623**

The welding attachment is used in combination with UCT-500 torch shank for brazing and gas welding.



## Product information

The selection of welding attachment with different gas flow rate / capacity will determine the workable material thickness range.

Size\* O-A 1250 for material thickness: 9.0 - 14.0 mm.

The size indicates consumption of Oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

## Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

## Documents

[SDoC and MD for IHM](#)

## Related products

Is accessory to

**500000**  
UCT-500 COMBINATION TORCH MASTER

Is part of bundle

**589861**  
GASWELDING CABINET COMPLETE

Is frequently bought together with

**510000**  
REGULATOR 510 OX PRESSURE 0-10 BAR

**174706**  
CUTTING NOZZLE 10- 25MM

**174722**  
CUTTING NOZZLE 50-100MM

**175356**  
CLEANING NEEDLES SET

**174672**  
ROLLER GUIDE STANDARD

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/welding-attachment-1250-l/>