

Product group: **170** Product number: **174581**

The welding attachment is used in combination with UCT-500 torch shank for brazing and gas welding.



## Product information

The selection of welding attachment with different gas flow rate / capacity will determine the workable material thickness range.

Size\* O-A230 for material thickness: 2.0 -3.0 mm

The size indicates consumption of Oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
--	----

## Documents

[SDoC and MD for IHM](#)

## Related products

### Is accessory to

**500000**  
UCT-500 COMBINATION TORCH MASTER  
**500001**  
UCT-500 COMBINATION TORCH COMPACT

### Is part of bundle

**589861**  
GASWELDING CABINET COMPLETE

### Is frequently bought together with

**510001**  
REGULATOR 510 AC PRESSURE 0-1.5 BAR  
**510000**  
REGULATOR 510 OX PRESSURE 0-10 BAR  
**174706**  
CUTTING NOZZLE 10- 25MM  
**234807**  
CUTTING ATTACHMENT 90 DGR  
**174573**  
WELDING ATTACHMENT 80L.

### This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing-cutting/welding-brazing-cutting-torch/welding-attachment-230-l/>