



WELDING ATTACHMENT 40 L

Product group: **170** Product number: **174565**

Size* O-A 40 Material thickness: <0,5 mm



Product information

Specification

General

| | |
|--|----|
| Invent Hazard Material (IMO/EU) classification | NA |
|--|----|

Technical data

The size indicates consumption of oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

Variants

| Product name | Product number |
|--|----------------|
| <u>FLASHBACK ARRESTOR FR-20 FOR AC+OX</u> | 619270 |
| <u>FLEX.WELD.ATTACHMENT 160L</u> | 183780 |
| <u>HEATING ATTACHMENT 5000 L</u> | 183756 |
| <u>MULTIFLAME HEATING ATTACHMENT 5000L</u> | 603399 |
| <u>SHANK NONRETURN VALVE F/6MM AC HOSE</u> | 597336 |
| <u>SHANK NONRETURN VALVE F/6MM OX HOSE</u> | 597344 |
| <u>SHANK NONRETURN VALVE F/9MM AC HOSE</u> | 651265 |
| <u>SHANK NONRETURN VALVE F/9MM OX HOSE</u> | 651257 |
| <u>SHANK W/NON-RETURN VALVES</u> | 174656 |
| <u>WELDING ATTACHMENT 1000 L</u> | 174615 |
| <u>WELDING ATTACHMENT 1250 L</u> | 174623 |
| <u>WELDING ATTACHMENT 230 L</u> | 174581 |
| <u>WELDING ATTACHMENT 40 L</u> | 174565 |
| <u>WELDING ATTACHMENT 400 L</u> | 174599 |
| <u>WELDING ATTACHMENT 650 L</u> | 174607 |
| <u>WELDING ATTACHMENT 80L</u> | 174573 |

Documents

[Supplier's declaration of Conformity \(SDoC\)](#)

Related products

Is accessory to

500000 UCT-500 COMBINATION TORCH MASTER

Is part of bundle

589861 GASWELDING CABINET COMPLETE

Is frequently bought together with

174599 WELDING ATTACHMENT 400 L

233601 AG 60 252 2.0 X 500MM 0,5KG

233551 FC-BRONZE 261 2.0 X500MM 1,0KG

174573 WELDING ATTACHMENT 80L

174698 CUTTING NOZZLE 3- 10MM

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/welding-attachment-40-l/>