

WELDING ATTACHMENT 650 L

 Product group: **170** Product number: **174607**

Size* O-A 650 Material thickness: 5-7mm



Product information

Specification

General

Technical data

Invent Hazard Material (IMO/EU) classification	NA
--	----

The size indicates consumption of oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

Variants

Product name	Product number
<u>FLASHBACK ARRESTOR FR-20 FOR AC+OX</u>	619270
<u>FLEX.WELD.ATTACHMENT 160L</u>	183780
<u>HEATING ATTACHMENT 5000 L</u>	183756
<u>MULTIFLAME HEATING ATTACHMENT 5000L</u>	603399
<u>SHANK NONRETURN VALVE F/6MM AC HOSE</u>	597336
<u>SHANK NONRETURN VALVE F/6MM OX HOSE</u>	597344
<u>SHANK NONRETURN VALVE F/9MM AC HOSE</u>	651265
<u>SHANK NONRETURN VALVE F/9MM OX HOSE</u>	651257
<u>SHANK W/NON-RETURN VALVES</u>	174656
<u>WELDING ATTACHMENT 1000 L</u>	174615
<u>WELDING ATTACHMENT 1250 L</u>	174623
<u>WELDING ATTACHMENT 230 L</u>	174581
<u>WELDING ATTACHMENT 40 L</u>	174565
<u>WELDING ATTACHMENT 400 L</u>	174599
<u>WELDING ATTACHMENT 650 L</u>	174607
<u>WELDING ATTACHMENT 80L</u>	174573

Related products

Is accessory to

500000 UCT-500 COMBINATION TORCH MASTER

500001 UCT-500 COMBINATION TORCH COMPACT

Is part of bundle

589861 GASWELDING CABINET COMPLETE

Is frequently bought together with

174573 WELDING ATTACHMENT 80L.

174656 SHANK W/NON-RETURN VALVES

175356 CLEANING NEEDLES SET

174581 WELDING ATTACHMENT 230 L

174599 WELDING ATTACHMENT 400 L

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/welding-attachment-650-l/>