

Last updated: 30/03/2023 21:02:26

WELDING ATTACHMENT 650 L

Product group: **170** Product number: **174607**

The welding attachment is used in combination with UCT-500 torch shank for brazing and gas welding.



Product information

The selection of welding attachment with different gas flow rate / capacity will determine the workable material thickness range.

Size* O-A 650 for material thickness: 5.0 -7.0 mm.

The size indicates consumption of Oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Variants

Product name	Product number
FLASHBACK ARRESTOR FR-20 FOR AC+OX	619270
FLEX.WELD.ATTACHMENT 160L	183780
HEATING ATTACHMENT 5000 L	183756
MULTIFLAME HEATING ATTACHMENT 5000L	603399
SHANK NONRETURN VALVE F/6MM AC HOSE	597336
SHANK NONRETURN VALVE F/6MM OX HOSE	597344
SHANK NONRETURN VALVE F/9MM AC HOSE	651265
SHANK NONRETURN VALVE F/9MM OX HOSE	651257
SHANK W/NON-RETURN VALVES	174656
WELDING ATTACHMENT 1000 L	174615
WELDING ATTACHMENT 1250 L	174623
WELDING ATTACHMENT 230 L	174581
WELDING ATTACHMENT 40 L	174565
WELDING ATTACHMENT 400 L	174599
WELDING ATTACHMENT 650 L	174607
WELDING ATTACHMENT 80L	174573

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

500001 UCT-500 COMBINATION TORCH COMPACT
500000 UCT-500 COMBINATION TORCH MASTER

Is part of bundle

589861 GASWELDING CABINET COMPLETE

Is frequently bought together with

174581	WELDING ATTACHMENT 230 L	175356	CLEANING NEEDLES SET
174599	WELDING ATTACHMENT 400 L		
174573	WELDING ATTACHMENT 80L.		
174656	SHANK W/NON-RETURN VALVES		

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/welding-attachment-650-l/?epieditmode=true&>