

Product group: 170 Product number: 174607

The welding attachment is used in combination with UCT-500 torch shank for brazing and gas welding.



Product information

The selection of welding attachment with different gas flow rate / capacity will determine the workable material thickness range.

Size* O-A650 for material thickness: 5.0 -7.0 mm.

The size indicates consumption of Oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

- 500000
UCT-500 COMBINATION TORCH MASTER
- 500001
UCT-500 COMBINATION TORCH COMPACT

Is part of bundle

- 589861
GASWELDING CABINET COMPLETE

Is frequently bought together with

- 174599
WELDING ATTACHMENT 400 L
- 174573
WELDING ATTACHMENT 80L.
- 174581
WELDING ATTACHMENT 230 L
- 174656
SHANK W/NON-RETURN VALVES
- 175356
CLEANING NEEDLES SET

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/welding-attachment-650-l/>