

Product group: 170 Product number: 174573

The welding attachment is used in combination with UCT-500 torch shank for brazing and gas welding.



Product information

The selection of welding attachment with different gas flow rate / capacity will determine the workable material thickness range.

Size* O-A80 for material thickness: 0.5 -1.0 mm

The size indicates consumption of Oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

Specification

General		Technical data
Invent Hazard Material (IMO/EU) classification		NA
		The size indicates consumption of oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

- 500000
UCT-500 COMBINATION TORCH MASTER
- 500001
UCT-500 COMBINATION TORCH COMPACT

Is part of bundle

- 589861
GASWELDING CABINET COMPLETE

Is frequently bought together with

- 510000
REGULATOR 510 OX PRESSURE 0-10 BAR
- 174706
CUTTING NOZZLE 10- 25MM
- 234807
CUTTING ATTACHMENT 90 DGR
- 174581
WELDING ATTACHMENT 230 L
- 175356
CLEANING NEEDLES SET

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/welding-attachment-80/>