

Product group: **170** Product number: **174573**

The welding attachment is used in combination with UCT-500 torch shank for brazing and gas welding.

## Product information

The selection of welding attachment with different gas flow rate / capacity will determine the workable material thickness range.

Size\* O-A80 for material thickness: 0.5 -1.0 mm

The size indicates consumption of Oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

## Specification

General	Technical data		
<table border="1"><tr><td>Invent Hazard Material (IMO/EU) classification</td><td>NA</td></tr></table>	Invent Hazard Material (IMO/EU) classification	NA	The size indicates consumption of oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.
Invent Hazard Material (IMO/EU) classification	NA		

## Documents

[SDoC and MD for IHM](#)

## Related products

Is accessory to

**500001**  
UCT-500 COMBINATION TORCH COMPACT  
**500000**  
UCT-500 COMBINATION TORCH MASTER

Is part of bundle

**589861**  
GASWELDING CABINET COMPLETE

Is frequently bought together with

**510000**  
REGULATOR 510 OX PRESSURE 0-10 BAR  
**174581**  
WELDING ATTACHMENT 230 L  
**174706**  
CUTTING NOZZLE 10- 25MM  
**234807**  
CUTTING ATTACHMENT 90 DGR  
**175356**  
CLEANING NEEDLES SET

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/welding-attachment-80/>