

Last updated: 30/04/2025 05:23:01

UNICOOL R-513A 11KG REFRIGERANT

Product group: **593** Product number: **905771**

A new generation of HFO/HFC blend refrigerant which is non-flammable and harmless to the ozone layer. Excellent low GWP refrigerant for medium temperature applications. Suitable for both new installation and existing R-134a system.



Product information

Features

- Non-flammable with a safety classification of A1
- Quality Guaranteed - purity and moisture content are guaranteed as per AHRI Standard 700.
- Global Availability - Products are available in WSS global network with the same specification and quality.
- No Performance Drop - it provides similar capacity to R-134a in medium temp. application.
- Suitable for new installation and retrofit.

Benefits

- Safety and Authenticity - Refrigerants delivered under the WSS Global Cylinder Ex-change program are fully traceable, safe, authentic, and thus eliminate the risks of receiving illegal or counterfeit refrigerants.
- Cost Effective- Reduce downtime and cost as the refrigerant is compatible with existing R-134a systems.
- Worldwide Compliance - This low GWP refrigerant solution enables ship owners to stay compliant with all international regulations.

Specification

General

| | |
|--|------|
| GWP | 631 |
| Invent Hazard Material (IMO/EU) classification | C-25 |
| ODP | 0 |

Dimensions/Weight

| | |
|-------------------------|--------|
| Connection [Size/ Type] | CGA660 |
| Diameter [mm] | 229 |
| Gross Weight [kg] | 20 |
| Height [mm] | 506 |
| Weight [kg] | 11 Net |

Documents

[SDoC and MD for IHM](#)

Related products

Accessories

- 544932**
REFRIGERANT CYL. VALVE ADAPTOR SET
- 597757**
CHARGING HOSE SET UCH-72 3X1.8M
- 711480**
DIGI-MANIFOLD SET (4-WAY)