Last updated: 30/04/2025 05:21:13



# MINIMIX 34 O2 12% IN 88% N2

Product group: **718** Product number: **630075** 

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture: - Minimix 34 is an aluminium disposable cylinder with 34 litres of gas - Minimix 58 is an aluminium disposable cylinder with 58 litres of gas

# Minimix Warning at Warning at Warning at the state of the

## **Product information**

Gas Composition:

Oxygen - 12%

Nitrogen (N2) - balance

Used with Regulator 620013

#### Features

- · Lightweight and disposable cylinder
- Compact size
- Comes standard with CGAC-10 connection
- Each cylinder delivered with a Certificate of Analysis
- Guaranteed and repeatable quality

#### Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easystock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

## **Specification**

General

Cylinder Type	Mnimix 34
Invent Hazard Material (IMO/EU) classification	NA

Dimensions/Weight

Connection [Size/ Type]	CGA C-10
Diameter [mm]	76
Height [mm]	289

# Technical data

Shelf life [months]	36
Volume (I)	0.9

### **Documents**

SDoC and MD for IHM

<u>media</u>

### **Related products**

Accessories

620013

REGULATOR F/SCOTTY VI AND 4COMP

# This page is printed from

https://www.wilhelmsen.com/zh-hans/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/disposables/minimix-34-o2-12-in-88-n2/lineary/spangases/disposables/minimix-34-o2-12-in-88-