

Last updated: 27/02/2023 07:19:01

Welding Cable and Drum

Unitor welding cable, type HO1N2D is designed for use in electric arc-welding machines and is made to be durable and flexible. Selection on welding cable size will depend on the max current capacity rating and duty cycle.



Product information

****Welding Cable**** The welding cable supplied by Unitor is recognized by its marking at regular intervals with the text: "Unitor oil resistant welding cable", size of cable, and the standard for oil resistant welding cable: H01N2-D.

****Cable drum**** The drum is supplied with brackets for bulkhead mounting. It has a folding crank which locks the drum from uncoiling the cable when the crank is folded inwards. Capacity up to approximately 100m 70mm² welding cable. Weight 10,5kg

Features

- The cable is oil resistant, flame resistant and wear resistant. The conductor is built up from 0.2 mm diameter copper wires to ensure high flexibility
- The cable complies with the harmonised standard HO1N2D for flexible welding cable
- Available in cross-section areas 35 mm², 50 mm² and 70 mm², in standard lengths of 10 m, 20 m and 50 m, fitted with Unitor safety connectors.
- When cable extensions with safety connectors are used the electrode holder and ground clamp with safety connectors should be used

Benefits

- Easy management and housekeeping of welding cables onboard
- The standard length cable extensions are fitted with Unitor safety cable connectors for optimal protection. Connection to the machine panel sockets is done with 2 pcs Dix/Unitor conversions, reducing risk of electric shocks or electrocution
- High quality and reliable for heavy duty welding onboard

Specification

Documents

[Cabledrum](#)

This page is printed from

<https://www.wilhelmsen.com/zh-hans/product-catalogue/products/welding-arc-welding-equipment/cables-and-connectors/welding-cable-and-drum/>